

LEDBeam 100 SW™

These 'Pure White' versions of the popular LEDBeam 100 fixture have been added to compliment the range of Pure White LEDWash products.

**Lichtquelle**

12x 15W smart/warm white multichips

**Lichtleistung**

3.620 (WW), 5.220 (CW) lux @ 5 m

**Zoombereich**

7°

**Effekte**

strobe effects, diffusion filters



The LEDBeam utilises 12 x 15 W LEDs to provide an extra punchy 7 degree beam or with the addition of the clip on 25 or 40 degree frost filter, a flat, smooth wash. Small enough to 'hide' within a set, the LEDBeam 100 is ideal for use on exhibitions or in retail environments where a powerful, quality light is required with the added benefits of low power consumption and no lamp replacement or maintenance cost. The motorised Pan and Tilt system is equally capable of dramatic fast movement as it is a subtle slow sweep. The SW version is adjustable between 2800-6300 K. Available only on request.

Technische Spezifikation

Lichtquelle

- Light source: 12 x 15 W Cool White/Warm White LED multi-chips
- Life Expectancy: > 60.000 hours max.
- Typical Lumen Maintenance: 70% @ 60.000 hours

Optisches System und Effekte

- High efficiency component optics
- Beam angle 7°
- White colour temperature: 2.800 K - 6.300 K
- High resolution dimmer 0-100%
- Strobe effect with variable speed (20 flashes per second max.)
- Pre-programmed random strobe & pulse effects
- Pan and Tilt range: 450°/300°

Steuerung und Programmierung

- User Interface: 2 line LCD display & 4 push buttons
- Protocols: DMX-512, RDM
- DMX Modes (channels): 6 (22, 14, 11, 9, 22, 24)
- 3 user defined programs, each up to 25 steps
- Stand-alone operation
- Data in/out: Locking 5-pin XLR
- Built-in analyser for easy fault finding

Thermische Spezifikation

- Maximum ambient temperature: 45 °C (113 °F)
- Maximum housing temperature: 75 °C (167 °F)

Elektrische Spezifikationen

- Supply input: 100-240 V AC, 50-60 Hz auto ranging
- Max. power consumption: 200 W
- Power connection: Neutrik PowerCon In/Out

Freigaben

- CE Compliant
- cETLus Compliant

Mechanische Spezifikationen

- Height: 314 mm (12.4")
- Width: 233 mm (9.2")
- Depth: 149 mm (5.9")
- Weight: 4 kg (8.8 lbs)

Rigging

- 1 x Omega bracket (included) with ¼-turn quick locks

Zubehör

- Top hat
- Diffusion filter 20°
- Diffusion filter 40°
- Power Cable - Neutrik Powercon Input (2 m length)
- Power Cable - Neutrik Powercon Link (2 m length)